

# LoadProbe 410



Ultrasonic device for one-channel preload measurement of bolted joints.

**intellifast** 

Siemensstraße 18  
67346 Speyer (Germany)  
Phone: +49 6232 9195 0  
Fax: +49 6232 9195 19  
info@intellifast.de  
www.intellifast.de

## Overview

- New **WiFi** connection to the external PC/tablet
- Works with the **new LoadView** software
- Optional Wind Edition equipment and battery pack

## Specifications\*

External connectors	LAN 1 Gbps, WiFi 802.11n
Battery	Lithium Ion up to 5h battery-life
Measurement rate	1 Hz
Power supply Input	AC 100-240 V, 1.5A, 50-60Hz
Power supply Output	DC 19V, 3.7A
Size	280 x 145 x 55 mm
Weight	2 kg
Operating ambient temperature	0 to 40° C

Relative humidity 5% to 95% non-condensing

\* The mentioned values are based on the manufacturer's specification. Subject to technical changes.

## What's in the Box

- LoadProbe 410 unit
- Measurement software **LoadView** (single license)
- WiFi antenna
- Standard magnetic ultrasonic probe, 5m cable
- Pt100 temperature probe, 5m cable
- Power supply
- Hard case
- Operating manual

## Optional

- External battery pack for up to 5h add. battery-life
- Wind Edition equipment:
  - Strong magnetic ultrasonic & temperature probes
  - Barcode reader for easy identification of bolts